



**WAVE**

*Anti-moisture Weighing Scale*

**Features:**

- IP 56 wash down design
- Digital calibration
- Double over-load protection
- Full range tare; Auto zero tracking
- Low power indication and auto power off
- Easily adjusted leveling feet for stability of the scale
- Curve-form base for easy carrying and handling
- Smooth surface and easy-to-disassemble platter for convenient maintenance
- Stainless steel platter
- Dry batteries model also available

WAVE (LCD, 5 keys): Kilogram (kg), gram (g), ounce (oz), and pound (lb) weighing unit available

**Options:**

- OIML approval model available for 1/3 000 display resolution
- Second display



**Specifications:**

• 1/6000 resolution model also available for non-approval model

MODEL	CAPACITY	DIVISION
WAVE -1.5	1.5 kg ( 3 lb)	0.5 g (0.001 lb)
WAVE -3	3 kg ( 6 lb)	1 g (0.002 lb)
WAVE -6	6 kg (12 lb)	2 g (0.005 lb)
WAVE -15	15 kg (30 lb)	5 g ( 0.01 lb)
WAVE -30	30 kg (60 lb)	10 g ( 0.02 lb)

**Operating Temperature:** -5°C ~ 40°C (23°F ~ 104°F); Approval model: -10°C ~ 40°C (14°F ~ 104°F)

**Power Supply:** DC10V/1A Adaptor + DC 6V/5AH Rechargeable Battery or 6 x R14 1.5V dry batteries (not included)

**Dimensions:** 250 x 140 x 300 mm (W x H x D)

**Platter Size:** 225 x 195 mm (W x D)

**Display:** WAVE: LCD, 6 digits, height 25 mm



**Distribuidor Autorizado**

Móvil: +593 98 635 3635  
 +593 99 830 8818  
 Fijo: +593 2 2550342  
 Email: info@ingematic.net  
 Quito - Ecuador

[www.ingematic.net](http://www.ingematic.net)