

YSW **IP68**

Waterproof Weighing Scale



YSW-5C



YSW-5E



EXCELL®

Since 1979



ISO 9001

FEATURES

IP68 CERTIFIED BY SGS

- ◆ Sealed waterproof silica gel strip blocks water from infiltrating into the scale.
- ◆ Surrounded by waterproof grade sheeting to ensure the water free.
- ◆ 1/3,000~1/7,500 display resolution available.
- ◆ Aluminum frames coated with anti-corrosion treatment for longer lifespan.
- ◆ LED or LCD display model available.
- ◆ Stainless steel made feet and platter for anti-rust.
- ◆ High speed of 24bits AD fast reacts and shortens the weighing operation duration.
- ◆ Selectable units: Kilogram (kg), gram (g), ounce (oz), and pound (lb) weighing units available.
- ◆ Built-in rechargeable battery can be easily replaced.
- ◆ Vertical placement design battery prevents from electrolyte leakage, and makes more safety and durable.
- ◆ Low power indication and auto power off.
- ◆ Well-designed protection point for transportation.
- ◆ Securable platter with screws at users' needs.

IP68



SPECIFICATION

MODEL	CAPACITY	DIVISION	RESOLUTION
YSW-3	3kg	0.5g	1/6,000
		1g	1/3,000
YSW-6	6kg	1g	1/6,000
		2g	1/3,000
YSW-15	15kg	2g	1/7,500
		5g	1/3,000
YSW-30	30Kg	5g	1/6,000
		10g	1/3,000

Display Specifications:

YSW-5C (LCD display): 109x35.5mm; 6 digits, 25mm (height), LED backlight

YSW-5E (LED display): 75.1x19mm; 6digits, 15mm (height)



Operating Temperature : 0°C ~ 40°C (32°F ~ 104°F)

Power Source :

AC 110V~240V (±10%) adapter + DC 6V / 7Ah or
DC 6V / 4Ah rechargeable battery

Dimensions: 250.4 x 144 x 313mm (W x H x D)

Weight of the scale: Around 3kg



**Distribuidor
Autorizado**

Móvil: +593 98 635 3635
+593 99 830 8818
Fijo: +593 2 2550342
Email: info@ingematic.net
Quito - Ecuador