

Double-Ended Beam Load Cell

FEATURES

- Capacities: 1k to 75k lbs
- Environmental protection: IP67 (DIN 40.050)
- Material: stainless steel
- Center loaded design
- Welded covers for all capacities
- **Optional**
 - FM certified versions are available for use in potentially explosive atmospheres



APPLICATIONS

- Silo, tank, hopper weighing
- Custom system designs
- Low capacity vehicle scales


DESCRIPTION

The Model 9203 is a stainless steel double-ended shear beam type load cell.

A reliable sealing and mechanical protection of the skin gage area is ensured by the use of a potting compound with a metal cover.

The center-loaded design results in minimal sensitivity to off-center forces.

OUTLINE DIMENSIONS in inches



Wiring

+Excitation	Red
- Excitation	Black
+Output	Green
- Output	White

CAPACITY	A ₁	A ₂	B	C	D	E	F	G	Thread
1k-5k	1.22	1.22	7.50	6.25	0.62	0.50	1.12	1.25	1/4-18NPT
10k-25k	1.44	1.94	8.75	7.50	0.62	0.81	1.62	1.99	1/4-18NPT
35k	1.44	2.44	8.75	7.50	0.62	0.81	1.62	2.50	1/4-18NPT
50k-75k	2.44	2.94	13.50	11.50	1.00	1.31	3.25	2.99	1/2-14NPT

Capacities are in pounds.

Double-Ended Beam Load Cell

SPECIFICATIONS		
PARAMETER	VALUE	UNIT
Standard capacities (E _{max})	1k, 1.5k, 2k, 2.5k, 5k, 10k, 15k, 20k, 25k, 35k, 50k, 75k	lbs
Accuracy class	Non Approved—D3	
Rated output (=S)	3.0	mV/V
Rated output tolerance	0.008	±mV/V
Zero balance	1.0	±% FSO
Combined error	0.03	±% FSO
Creep error (20 minutes)	0.03	±% FSO
Temp. effect on min. dead load output	0.0015	±% FSO/5°C (°F)
Temperature effect on sensitivity	0.0008	±% FSO/5°C (°F)
Maximum safe overload	150	% E _{max}
Ultimate overload	300	% E _{max}
Maximum safe side load	100	% E _{max}
Excitation voltage	10	V
Maximum excitation voltage	15	V
Input resistance	700±14	Ω
Output resistance	703±4	Ω
Insulation resistance	≥1000	MΩ
Compensated temperature range	-10 to +40 (+14 to +104)	°C (°F)
Operating temperature range	-18 to +65 (0 to +150)	°C (°F)
Element material (DIN)	Stainless steel	
Sealing	IP67	

FSO— Full Scale Output

All specifications subject to change without notice.

www.ingematic.net

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.